

4293-04

DIRECTIONS FOR USE:


This product must be used in accordance to the following directions by HVACR professionals only.

1. Shake can for 30 second before using.
2. PRODUCT IS FLAMMABLE DURING DISPENSING.

Before application, surface should be free of all foreign material. Wear eye protection and rubber or plastic gloves during use. Apply between 60° and 100°F.

3. To assemble, push and rotate extension tube firmly onto trigger; screw trigger assembly onto valve.
4. HOLD CAN UPSIDE DOWN and activate trigger while directing tube into area to be filled. NEVER ACTIVATE VALVE WITH CAN RIGHT SIDE UP. This allows propellant to escape prematurely.
5. Fill cavity only 2/5 (40%) full; foam will expand

6. TACK-FREE IN 30 MINUTES; DRIES IN 4 HOURS AT 70°F AND 40-50% R.H.
7. After Nu-Foam has completely dried (approx. 4 hours), it can easily be painted, sanded or caulked. To protect Nu-Foam against ultraviolet deterioration, always paint exposed foam when used on outside applications.
8. To prevent hardening of foam in valve stem and trigger, carefully unscrew trigger from can valve and clean both immediately with acetone or solvent remover. Replace cap and STORE IN UPRIGHT POSITION.



CAN MUST BE UPRIGHT WHEN NOT IN USE



DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

PREVENTION: Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. [In case of inadequate ventilation] wear respiratory protection.

RESPONSE: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing. Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

DISPOSAL: Dispose of contents/container in accordance with local authority requirements.

KEEP OUT OF REACH OF CHILDREN.



Made in U.S.A.
 Manufactured for:
 Nu-Calgon
 2611 Schuetz Rd.
 St. Louis, MO 63043
 Customer Service: 800-554-5499
 Chemical Emergency: 800-424-9300
 www.nucalgon.com
 (119) Calgon is a licensed trade name.

Nu-Foam®

EXPANDING & INSULATING SEALANT

No CFCs, No HCFCs

469 Linear Feet of a 3/8" Bead
More Than Most Competitive Cans

Insulates Against Heat Loss and Heat Gain

Seals Cracks, Holes and Other Voids

Deadens Sound



-
- KEEP OUT OF REACH
- OF CHILDREN.
- Read carefully other
- cautions on back panel.
-

DANGER:

EXTREMELY FLAMMABLE.

CONTENTS UNDER PRESSURE.

FOR PROFESSIONAL USE ONLY

NET WT. 12 OZ. (341 GRAMS)