

FOR USE ON WET OR DRY SURFACES:

Pan-Spray is an easy-to-use spray that makes a waterproof, flexible patch in condensate pans, cooling towers and many other applications. Helps seal out rust and corrosion. Perfect for emergency repairs.

DIRECTIONS FOR USE: This product must be used in accordance to the following directions by HVACR professionals only.

SHAKE FOR A MINIMUM OF 30 SECONDS. Apply to clean surface. Spray surface with short, even strokes from a distance of 10 to 12 inches. Apply until thoroughly coated. For large holes or cracks apply Pan-Spray around edge of leak, then place a mesh material over leak before final coating is applied. For best results product should be used at room temperature and applied to a clean surface void of all loose debris. After use, clean spray valve tip by inverting can and spraying until only propellant comes out. Cleanup with mineral spirits or paint thinner.

Risk to your health depends on level and duration of exposure. Use this product outdoors if possible. If you must use indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. Avoid contamination of food. Avoid contact with eyes or prolonged contact with skin.

CONTAINS (CAS NO): Heptane (142-82-5), Toluene (108-88-3), Dimethyl Ether (115-10-6), Acetone (67-64-1), and Isopropanol (67-63-0).

May affect the brain or nervous system causing dizziness, headache or nausea. May cause eye, skin, and nose and throat irritation. Harmful if swallowed. **CONTENTS UNDER PRESSURE.** Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. Store in cool area. Do not freeze.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flame and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors; spray mist, sanding dust, or over spray. Ensure fresh air entry during application. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Do not use in basement or other unventilated areas.

DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves, protective clothing and eye protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe gas. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product.

RESPONSE: If exposed or concerned: Get medical advice/attention. **If on skin:** Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **If inhaled:** remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE if you feel unwell. **If swallowed:** Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. **STORAGE:** Store locked up. Keep container tightly closed. **Keep out of reach of children.** **DISPOSAL:** Dispose of container in accordance with local, regional, national and international regulations.

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Made in Canada.
 Manufactured for:
 Nu-Calgon
 2611 Schuetz Rd.
 St. Louis, MO 63043
 Customer Service: 800-554-5499
 Chemical Emergency: 800-424-9300
www.nucalgon.com
 (419) Calgon is a licensed trade name.

Pan-Spray®

LEAK SEALER & PATCH PRODUCT

BLACK COLOR

Rubberized Coating

Complete Waterproof Seal

Won't Chip, Crack, Flake or Peel

For Condensate Pans, Cooling Towers, Swamp Coolers, Plumbing, & Pipe Fixtures



Covers Up to 20 Square Feet

DANGER:

- EXTREMELY FLAMMABLE
 - LIQUID AND VAPOR.
 - VAPOR HARMFUL.
 - EYE AND SKIN IRRITANT.
 - HARMFUL OR FATAL IF SWALLOWED.
 - CONTENTS UNDER PRESSURE.
- KEEP OUT OF REACH OF CHILDREN.
 - See back panel for additional precautionary statements.
 - FOR PROFESSIONAL USE ONLY**

NET WT. 16 OZ. (454 GRAMS)