

This product is ideal for providing a moisture barrier for refrigeration and air conditioning lines, and cold water pipes, etc. Sweating and dripping are eliminated by this durable, waterproof protective barrier. It separates the warm moist air and the cold surface, preventing condensation from occurring. Pipe-Dri offers the ability to apply on odd shaped fittings and hard to reach areas. Reapplication will continue to build thickness as required. One can will normally cover approximately ten feet of one inch water pipe or eight square feet of flat surface area with two coats. Ideally, the product should be at room temperature (70-75°F) and the surface to be coated at a lower temperature. A thick application is hard to form on warmer surfaces (above 80°F); however, a thicker coat may be achieved by applying 2 or more light coats. Once a coating has been allowed to dry and harden, it will be stable at temperatures up to 120°F. **DO NOT USE ON PLASTICS OR PAINTED SURFACES.**

#### **DIRECTIONS FOR USE:**

**This product must be used in accordance to the following directions by HVACR professionals only.**

1. Wipe excess dirt and moisture from surface to be sprayed.
2. Shake can well and remove protective cap.
3. Hold can upright about 12 inches from surface with valve opening pointed away. Apply a thin first coat.
4. Allow to dry (5 to 10 minutes); if second coat is needed, reapply from a distance of 6-10 inches.

#### **DANGER**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

**PREVENTION:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe gas. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**RESPONSE: If swallowed:** Call a poison center/doctor if you feel unwell. Rinse mouth. **If on skin:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.

**STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up. **KEEP OUT OF REACH OF CHILDREN.**

**DISPOSAL:** Dispose of contents/container in accordance with local/regional/national/international regulations.

5. When finished, invert can and spray for 1-2 seconds to clean nozzle.

**NOTE:** Product is designed for cold piping systems only. **Per CARB Sec 92522(e), this product is prohibited for sale and use in the state of California.**

**CONTAINS (CAS NO):** Methylene Chloride (75-09-2), Octadecanoic Acid (57-11-4), Petroleum gases, liquefied, sweetened (68476-86-8) and Zinc Stearate (557-05-1). Methylene Chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on the level and duration of exposure. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. **Reduces the blood's oxygen-carrying capacity.** May cause eye, skin, and nose and throat irritation. Harmful if swallowed.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Ensure fresh air entry during application. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing.



4297-75

Nu-Calgon

# Pipe-Dri®

**COLD PIPE INSULATION SPRAY**

***Stops Sweating and Dripping***

**Provides a Moisture Barrier on:**

**Refrigeration Lines**

**Air Conditioning Lines**

**Cold Water Pipes and  
Other Cold Surfaces**



## **DANGER:**

EXTREMELY  
FLAMMABLE LIQUID  
AND VAPOR  
VAPOR HARMFUL  
CONTENTS UNDER  
PRESSURE  
HARMFUL OR FATAL  
IF SWALLOWED  
CAUSES EYE BURNS  
CAUSES SKIN  
IRRITATION

KEEP OUT OF REACH  
OF CHILDREN.  
See back panel for  
additional precautionary  
statements.

**FOR PROFESSIONAL  
USE ONLY**



Made in Canada.  
Manufactured for: Nu-Calgon  
2611 Schuetz Rd. • St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com • (818) Calgon is a licensed trade name.

**NET WT. 18 OZ. (511 GRAMS)**