

4083-90

DuraCoil

COIL & SURFACE PROTECTANT

*Long Lasting Coating for Coils
In Corrosive Environments*

**Heresite® Nonflat Dual
Function Coating & Primer**

**Causes Negligible
Heat Transfer Loss**

**Fast, Air-Dry Formula
Bonds to All Metals**

BROWN COLOR

KEEP OUT OF REACH
OF CHILDREN
Read label before use
**FOR PROFESSIONAL
USE ONLY**



**USE FOR
OEM
COATING
REPAIR!**

DANGER:
EXTREMELY
FLAMMABLE AEROSOL

FEATURES: DuraCoil is a field proven coating developed to extend the service life of an installed air conditioning coil or metal component in a corrosive environment. Coils located in coastal regions, industrial/ agriculture production settings or refrigeration applications to protect against corrosive food acids are ideal applications if an OEM coating was not applied or has been compromised over time in service.

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

1. Coil must be clean and dry – free of dust, dirt, grease and grime. Clean with a Nu-Calgon coil cleaner if necessary. Remove any equipment panels necessary to properly apply product. Cover any adjoining surfaces that need to be protected. Please note the product is a brown colored coating – ensure acceptability.

2. Disconnect all power to the equipment before use. Do not spray near sparks, heat or open flame.
3. Use only with adequate ventilation; avoid breathing of vapors and spray.
4. For best results, spray when the outdoor temperature is 50°F or above.
5. Shake the canister for one minute after you hear the mixing ball rattle.
6. Apply coating in several thin even coats over the coil or metal surface.
7. Allow adequate drying time before turning on the system.

Note: For future coil cleanings after DuraCoil has been applied, consider Nu-Calgon coil cleaners such as Tri-Pow'r, Special HD CalClean, CalClean, Cal-Green, Evap-Green, Evap-Pow'r, TriClean 2x, or Green Clean. For additional questions, please contact Nu-Calgon.



DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

RESPONSE: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. If skin irritation occurs; Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.

STORAGE: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Keep container tightly closed.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations.



Aerosol Coating Category and Limit:
Nonflat Coating - 0.95

WARNING: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Made in the U.S.A.
Manufactured for:
Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(618) Calgon is a licensed trade name.

Heresite® is registered trademark of
Heresite Protective Coatings.

NET WT. 11 OZ. (312 GRAMS)