



4184-53

# Fluorescent Gas Leak Detector

**MICRO LEAK DETECTOR**

*Fluorescent Color for Easier Locating*

Fluorescent Gas Leak Detector is the complete gas leak detector for today's service technician. The product, formulated to maintain **long lasting bubbles**, finds the smallest leaks in the system since it clings to surfaces for superior contact time. It is ideal for use in and around **food processing areas**; remove or cover all food products during use. Non-corrosive to metals. Use freely on systems with fluorescent dyes as Fluorescent Gas Leak Detector will not interfere with the use of ultraviolet or blacklight detection. Suitable for use on any pressurized refrigerant system, natural gas or oxygen line. Fluorescent Gas Leak Detector is oxygen safe. **Freeze protected down to 5°F (and will handle up to 225°F).**

**DIRECTIONS FOR USE:**

**This product must be used in accordance to the following directions by HVACR professionals only.**

Apply a uniform coating liberally on the surfaces wherever leaks are suspected. Visually examine surfaces for signs of foam or small bubble formation. Be patient - wait a minimum of 5 minutes. Check bottom of all fittings for increased bubbles/foam. If a leak is found, consider Nu-Calgon's EasySeal if the situation is appropriate.



**FOR PROFESSIONAL USE ONLY**

**8 fl. oz. (237mL)**

**PREVENTION:** Observe good industrial hygiene practices.

**RESPONSE:** Wash hands after handling.

**KEEP OUT OF REACH OF CHILDREN.**

**STORAGE:** Store away from incompatible materials.

**DISPOSAL:** Dispose of waste and residues in accordance with local authority requirements.

Contains: Propylene Glycol (CAS# 57-55-6).



2611 Schuetz Rd. | St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(319) Calgon is a licensed trade name.