

- Dissolves contaminants in seconds
- Dries at a controlled rate-leaves no residue
- Restoration time will vary based on soil load
- Non corrosive to metal surfaces
- Easy-to-use

Description

Soak-N-Solv is a unique ready-to-use restoring compound, specially formulated for HVACR components. Soak-N-Solv dissolves contaminants in seconds, dries at a controlled rate and leaves no residue. The formula is non corrosive to metal surfaces, and is easy to use on a variety of components.

Application

This product must be used in accordance to the following directions by HVACR professionals only.

Use Soak-N-Solv to restore internal assemblies of TEVs, solenoid valves, PRVs and other refrigerant flow devices. Soak-N-Solv can also be used to restore metal parts of a compressor rebuild, fan blades, flange assemblies, fasteners and other HVACR related components.

Instructions

For spot treatment, apply undiluted Soak-N-Solv with a rag, brush, or applicator. Heavily soiled or greasy components can be soaked in a container of Soak-N-Solv. If necessary, rinse with a second treatment of Soak-N-Solv. Repeat as necessary.

Warnings

Protect rubber, fiberglass, and plastic parts when using Soak-N-Solv. Keep away from open flames and other ignition sources, and do not smoke while using. Use in a well ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. Keep container tightly closed when not in use.

Specialty Product

Soak-N-Solv™



Read and understand the product's label and Safety Data Sheet ("SDS") for precautionary and first aid information. The SDS is available on the Nu-Calgon website at www.nucalgon.com.


Properties

Color	Colorless
Odor	Solvent
Foaming	None
Solubility	330 g/l (20°C)
Flash Point	> -22.0°F (> -30.0°C)
Initial Boiling Point	108.14°F (42.3°C)

Packaging

1 quart 4162-77

BEFORE



AFTER

