

NuLock™ (P/N: 4289-01) is a fast curing, medium strength, hard-set anaerobic thread-locking compound for bonding and sealing threads, and retaining of cylindrical parts. For threaded fasteners up to 3/4" inch in diameter. NuLock is highly resistant to heat, vibrations and many chemicals. Handling time of 10 minutes, functionally cures in 1-3 hours, fully cures in 24 hours. Temperature range between -65°F to 300°F. Meets US Military specifications.

DIRECTIONS: For Professional use only, use PPE. Surfaces should be dry, clean, and free of any contamination. Apply NuLock to male threads. Nu-Lock performs the best in thin bond gaps. Assemble the threaded assemblies normally and allow NuLock to cure.

WARNING: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolong or repeated exposure.



PREVENTION: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell. Dispose of contents/container to local/regional/national/international regulations.

Contains: cumene hydroperoxide (CAS # 80-15-9)



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(0620) Calgon is a licensed trade name.