

NuLock (P/N: 4289-04) is a high performance anaerobic sealant for sealing close gaps (up to 0.25mm) in rigid metal faces and flanges used in the HVAC/R market. Excellent thixotropic property prevents migration of the sealant before or during curing. Good shock and vibration resistance. Handling cure time of 15-90 minutes; functionally cures in 3-6 hours, fully cures in 24 hours. Temperature range between -65°F to 300°F. Meets US Military specifications.

DIRECTIONS: For professional use only, use PPE. Surfaces should be dry, clean, and free of any contamination. Product is formulated for close fitting flanged parts with gaps up to 0.25mm. Low pressure may be used to confirm a complete seal immediately after assembly and before curing. Flanges should be tighten as soon as possible after assembly to avoid any shimming.

WARNING: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.



PREVENTION: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Dispose of contents/container to local/regional/national/international regulations.



6 81001 00025 3

Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(0620) Calgon is a licensed trade name.