

FEATURES: DuraCoil is a field proven coating developed to extend the service life of an installed air conditioning coil or metal component in a corrosive environment. Coils located in coastal regions, industrial/agriculture production settings or refrigeration applications to protect against corrosive food acids are ideal applications if an OEM coating was not applied or has been compromised over time in service. Designed for coils in corrosive environments, the non-flat dual function coating and primer causes negligible heat transfer loss.

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

1. Coil must be clean and dry – free of dust, dirt, grease and grime. Clean with a Nu-Calgon coil cleaner if necessary. Remove any equipment panels necessary to properly apply product. Cover any adjoining surfaces that need to be protected. Please note the product is a gray colored coating

DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause cancer. Causes serious eye irritation. May cause genetic defects. May cause harm to breast-fed children. Causes skin irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy and while nursing. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep container tightly closed.

RESPONSE: IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** Wash with plenty of water. Take off contaminated clothing. And wash it before reuse. If skin irritation or a rash occurs: Get medical advice/attention. Get Medical advice/attention if you feel unwell. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. **STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place. Store locked up. **DISPOSAL:** Dispose of contents/container in accordance with local/ regional/national/international regulations. **KEEP OUT OF REACH OF CHILDREN. Contains (CAS#):** Petroleum gases, liquefied, sweetened (68476-86-8), Aliphatic, light hydrocarbon solvent (64742-89-8), Isoparaffinic petroleum distillate (64742-47-8), Acetone (67-64-1), TALC (14807-96-6), Wollastonite (13983-17-0), Titanium dioxide (13463-67-7), Butylated hydroxytoluene (128-37-0), Sodium alumina (57455-37-5), Silica, amorphous (7631-86-9), Octane (111-65-9), n-Heptane (142-82-5), Quartz (14808-60-7), Propylene glycol monomethyl ether (107-98-2).

- ensure acceptability.
- 2. Disconnect all power to the equipment before use. Do not spray near sparks, heat or open flame.
- 3. Use only with adequate ventilation; avoid breathing of vapors and spray.
- 4. For best results, spray when the outdoor temperature is 50°F or above.
- 5. Shake the canister for one minute after you hear the mixing ball rattle.
- 6. Apply coating in several thin even coats over the coil or metal surface.
- 7. Allow adequate drying time before turning on the system.

Note: For future coil cleanings after DuraCoil has been applied, consider Nu-Calgon coil cleaners such as Tri-Pow'r, Special HD CalClean, CalClean, Cal-Green, Evap-Green, Evap-Pow'r, TriClean 2x, or Green Clean. For additional questions, please contact Nu-Calgon.



4083-91



DuraCoil

COIL & SURFACE PROTECTANT

Long Lasting Coat



**Coat & Primer
Fast Drying
Bonds to All
Metals**

**USE FOR OEM
COATING REPAIR!**

GRAY COLOR



Aerosol Coating Category and
Limit: Nonflat Coating: 0.95



Manufactured for:
Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com

(1121) Calgon is a licensed trade name.

WARNING: This product can expose you to chemicals including Silica, Amorphous which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

DANGER:
EXTREMELY
FLAMMABLE AEROSOL

- KEEP OUT OF REACH
- OF CHILDREN
- Read label before use
- **FOR PROFESSIONAL USE ONLY**

NET WT. 11 OZ. (312 GRAMS)