

4297-76

This product is ideal for providing a moisture barrier for refrigeration and air conditioning lines, and cold water pipes, etc. Sweating and dripping are eliminated by this durable, waterproof protective barrier. It separates the warm moist air and the cold surface, preventing condensation from occurring. Pipe-Dri offers the ability to apply on odd shaped fittings and hard to reach areas. Reapplication will continue to build thickness as required. One can will normally cover approximately ten feet of one inch water pipe or eight square feet of flat surface area with two coats.

Ideally, the product should be at room temperature (70-75°F) and the surface to be coated at a lower temperature. A thick application is hard to form on warmer surfaces (above 80°F); however, a thicker coat may be achieved by applying 2 or more light coats. Once a coating has been allowed to dry and harden, it will be stable at temperatures up to 120°F. **DO NOT USE ON PLASTICS OR PAINTED SURFACES.**

**DANGER**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.



**PREVENTION:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection.

**RESPONSE: IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **STORAGE:** Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. **DISPOSAL:** Dispose of container in accordance with local, regional, national and international regulations.

**KEEP OUT OF REACH OF CHILDREN**

**WARNING:** This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**DIRECTIONS FOR USE:**

**This product must be used in accordance to the following directions by HVACR professionals only.**

1. Wipe excess dirt and moisture from surface to be sprayed.
2. Shake can well and remove protective cap.
3. Hold can upright about 12 inches from surface with valve opening pointed away. Apply a thin first coat.
4. Allow to dry (5 to 10 minutes); if second coat is needed, reapply from a distance of 6-10 inches.
5. When finished, invert can and spray for 1-2 seconds to clean nozzle.

**NOTE:** Product is designed for cold piping systems only.

**CONTAINS (CAS#):** Acetone (67-64-1), Petroleum gases, liquefied, sweetened (68476-86-8), Octadecanoic acid (57-11-4), Octadecanoic acid, zinc salt (557-05-1).

Flat Coating: 0.80

# Pipe-Dri®

**COLD PIPE INSULATION SPRAY**

*Stops Sweating and Dripping*

**Provides a Moisture Barrier on:**

- Refrigeration Lines
- Air Conditioning Lines
- Cold Water Pipes and Other Cold Surfaces



**DANGER:**

EXTREMELY  
FLAMMABLE  
AEROSOL

CONTENTS UNDER  
PRESSURE

CAUSES SERIOUS  
EYE IRRITATION

KEEP OUT OF REACH  
OF CHILDREN.  
See back panel  
for additional  
precautionary  
statements.

**FOR PROFESSIONAL  
USE ONLY**

Made in Canada with globally sourced materials.  
Manufactured for:  
Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
[www.nucalgon.com](http://www.nucalgon.com)  
(0221) Calgon is a licensed trade name.



**NET WT. 14 OZ. (397 GRAMS)**