

SECTION 1 Identification

1.1. GHS Product identifier

Product form	: Mixture
Product name	: Electrical Contact Cleaner
Product code	: 4082-03
Vaporizer	: Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Electrical Contact Cleaner

1.4. Supplier's details

Manufacturer

Nu-Calgon
2611 Schuetz Road
St. Louis, MO
63043
US
T 314-469-7000 / 800-554-5499
www.nucalgon.com

1.5. Emergency phone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Germ cell mutagenicity, Category 1B	May cause genetic defects.
Carcinogenicity, Category 1B	May cause cancer.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	May be fatal if swallowed and enters airways.

2.2. GHS label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US)



Signal word (GHS CA/US)

: Danger

Hazard statements (GHS CA/US)

: Extremely flammable aerosol
Pressurized container; may burst if heated
May be fatal if swallowed and enters airways

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Precautionary statements (GHS CA/US)	<p>Causes skin irritation May cause drowsiness or dizziness May cause genetic defects. May cause cancer.</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. IF exposed or concerned: Get medical advice or attention. IF SWALLOWED: Immediately call a POISON CENTER or a doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor if you feel unwell. Specific treatment (see supplemental first aid instruction on this label). Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p>
--------------------------------------	--

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
1,1-Difluoroethane	Ethane, 1,1-difluoro- / Ethylidene difluoride / Fluorocarbon 152a / Halocarbon 152A / HFC 152a / Refrigerant gas R 152a / HFC-152a / Hydrofluorocarbon 152a / Freon 152a / HYDROFLUOROCARBON 152A / 1,1-Difluoroethylene	CAS-No.: 75-37-6	45 - 70

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Name	Chemical name / Synonyms	Product identifier	%
Naphtha, petroleum, hydrotreated light	Naphtha (petroleum), hydrotreated light / Naphtha, petroleum, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4-11 and boiling in the range of approximately minus 20-190°C.) / Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	CAS-No.: 64742-49-0	10 – 30
Solvent naphtha, petroleum, light aliphatic	Solvent naphtha (petroleum), light aliph., Low boiling point naphtha, [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).] Naphtha, petroleum, light aliphatic / Solvent naphtha light aliphatic / Naphtha, light aliphatic solvent / Solvent naphtha(petroleum), light aliphatic / Light aliphatic solvent naphtha / Solvent naphtha (petroleum), light aliphatic; Low boiling point naphtha [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).]	CAS-No.: 64742-89-8	10 – 30
n-Heptane	heptane, n-heptane Heptane (n-) / Heptane / Normal heptane / Heptane, n- / HEPTANE	CAS-No.: 142-82-5	10 – 30
Heptane, branched, cyclic and linear	-	CAS-No.: 426260-76-6	10 – 30

Comments

: CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of December 2022.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person.
First-aid measures general	: Call a physician immediately. If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Prolonged inhalation may be harmful. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Direct contact with eyes may cause temporary irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Aspiration of the product into the lungs may cause very serious pneumonia. May cause stomach distress, nausea or vomiting.
Chronic symptoms	: May cause genetic defects. May cause cancer.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. Treat symptomatically.
-----------------------------------	---

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical. Carbon dioxide. Foam.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.
Explosion hazard	: Pressurized container: may burst if heated. No direct explosion hazard.
Hazardous decomposition products in case of fire	: May include and are not limited to: oxides of carbon.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: In case of fire: Stop leak if safe to do so. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In the event of a significant spillage : Notify authorities if product enters sewers or public waters. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
------------------	--

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Environmental precautions

: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment

: Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up

: Pick up spilled material and collect it in a suitable container for disposal. . Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.

Other information

: This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing spray. Do not taste or swallow. Ensure good ventilation of the work station. Handle and open container with care.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Store this product upright in a cool, dry area, away from direct sunlight and heat. Store away from incompatible materials (see Section 10 of the SDS). Store locked up.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Naphtha, petroleum, hydrotreated light (64742-49-0)

Canada (Manitoba) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Newfoundland and Labrador) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Nova Scotia) - Occupational Exposure Limits

OEL TWA	100 ppm
---------	---------

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Naphtha, petroleum, hydrotreated light (64742-49-0)

Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Prince Edward Island) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Canada (Manitoba) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Newfoundland and Labrador) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Nova Scotia) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Canada (Prince Edward Island) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

n-Heptane (142-82-5)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	1640 mg/m ³
	400 ppm
OEL STEL	2050 mg/m ³
	500 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VECD (OEL STEV)	500 ppm
VEMP (OEL TWAEV)	400 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	400 ppm
OEL STEL	500 ppm (Heptane, all isomers)
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

n-Heptane (142-82-5)	
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	400 ppm
	500 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	1600 mg/m ³
	400 ppm
OEL STEL	2000 mg/m ³
	500 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	2000 mg/m ³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Environmental exposure controls : Avoid release to the environment.

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing. As required by employer code.

Respiratory protection:

Use respiratory protection. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Colourless
Odor	: Mild hydrocarbon
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 6.70505 lb/gal (Density VOC: 2.95054 lb/gal)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: Pressurized container: may burst if heated. Not explosive.
Oxidizing properties	: Not oxidising.
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 44.0048 % (353.56300 g/L)
-------------	-----------------------------

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

SECTION 10 Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong oxidizing agents. Acids. Reducing agents.
Hazardous decomposition products	: May include and are not limited to: oxides of carbon.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,1-Difluoroethane (75-37-6)

LC50 Inhalation - Rat [ppm]	437500 ppm/4h
ATE CA (Gases)	437500 ppmV/4h

Naphtha, petroleum, hydrotreated light (64742-49-0)

LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg (Source: IUCLID)
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm/4h
ATE CA (Dermal)	2800 mg/kg body weight
ATE CA (Gases)	73680 ppmV/4h

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)
ATE CA (Dermal)	3000 mg/kg body weight

n-Heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)
LC50 Inhalation - Rat	> 73.5 mg/l/4h
ATE CA (Dermal)	3000 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

STOT-repeated exposure : Not classified

Naphtha, petroleum, hydrotreated light (64742-49-0)

LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
---	---

NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
---	--

n-Heptane (142-82-5)

LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
---	---

NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
---	--

Aspiration hazard

: May be fatal if swallowed and enters airways.

Likely routes of exposure

: Skin and eye contact. Ingestion. Inhalation.

Symptoms/effects after inhalation

: Prolonged inhalation may be harmful. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact

: Direct contact with eyes may cause temporary irritation.

Symptoms/effects after ingestion

: May be fatal if swallowed and enters airways. Aspiration of the product into the lungs may cause very serious pneumonia. May cause stomach distress, nausea or vomiting.

Chronic symptoms

: May cause genetic defects. May cause cancer.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : See below for route-specific details.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

1,1-Difluoroethane (75-37-6)

LC50 - Fish [1]	295.783 mg/l Test organisms (species): other:
-----------------	---

LC50 - Fish [2]	719.611 mg/l Test organisms (species):
-----------------	--

EC50 - Other aquatic organisms [1]	146.695 mg/l Test organisms (species): other:
------------------------------------	---

EC50 96h - Algae [1]	168.276 mg/l Test organisms (species):
----------------------	--

Naphtha, petroleum, hydrotreated light (64742-49-0)

LC50 - Fish [1]	8.41 mg/l (Exposure time: 96 h - Species: <i>Oncorhynchus mykiss</i> [semi-static, closed] Source: ECHA)
-----------------	--

NOEC (chronic)	0.17 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
----------------	---

LOEC (chronic)	0.32 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
----------------	---

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

EC50 72h - Algae [1]	4700 mg/l (Species: <i>Pseudokirchneriella subcapitata</i>)
----------------------	--

n-Heptane (142-82-5)

LC50 - Fish [1]	375 mg/l (Exposure time: 96 h - Species: Cichlid fish)
-----------------	--

EC50 - Crustacea [1]	1.5 mg/l Test organisms (species): <i>Daphnia magna</i>
----------------------	---

NOEC (chronic)	0.17 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
----------------	---

LOEC (chronic)	0.32 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
----------------	---

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

12.2. Persistence and degradability

Electrical Contact Cleaner	
Persistence and degradability	Rapidly degradable
1,1-Difluoroethane (75-37-6)	
Persistence and degradability	Rapidly degradable
Naphtha, petroleum, hydrotreated light (64742-49-0)	
Persistence and degradability	Rapidly degradable
Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
Persistence and degradability	Rapidly degradable
n-Heptane (142-82-5)	
Persistence and degradability	Rapidly degradable
Heptane, branched, cyclic and linear (426260-76-6)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

n-Heptane (142-82-5)	
Partition coefficient n-octanol/water (Log Pow)	4.66

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of the material collected according to regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection.

SECTION 14 Transport information




In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
UN1950	UN1950	1950	1950
14.2. UN Proper Shipping Name			
AEROSOLS	Aerosols	AEROSOLS	Aerosols, flammable

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

TDG	DOT	IMDG	IATA
Transport document description			
UN1950 AEROSOLS, 2.1	UN1950 Aerosols, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)			
LTD QTY	LTD QTY	LTD QTY	LTD QTY Y
			
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN1950
Excepted quantities (TDG) : E0
Emergency Response Guide (ERG) Number : 126

DOT

UN-No. (DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provision (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

14.7. Transport in bulk according to Annex II of MARPOL 73/789(^9) and the IBC Code(^10)

Not applicable

SECTION 15 Regulatory information

All components of this product are present on DSL

Benzene (71-43-2)

Toxic Substance (CEPA – Schedule I)	Yes
-------------------------------------	-----

Naphthalene (91-20-3)

Toxic Substance (CEPA – Schedule I)	Yes
-------------------------------------	-----

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Ethylbenzene (100-41-4)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

Benzene (71-43-2)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	10 lb received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule
-----------	---

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

Naphthalene (91-20-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

Electrical Contact Cleaner

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Isopropylbenzene (98-82-8)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

 **WARNING:**

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

Issue date : 09/10/2025

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

Prepared by: Nu-Calgon Technical Service Phone: (314) 469-7000.

The information in the safety data sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.