

### SECTION 1 Identification

#### 1.1. GHS Product identifier

Product form	: Mixture
Product name	: Degreasing Solvent LV
Product code	: 4083-83
Vaporizer	: Aerosol

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Removes Grease and Oil
-----------------	--------------------------

#### 1.4. Supplier's details

##### Manufacturer

Nu-Calgon  
2611 Schuetz Road  
St. Louis, MO  
63043  
US  
T 314-469-7000 / 800-554-5499  
[www.nucalgon.com](http://www.nucalgon.com)

#### 1.5. Emergency phone number

Emergency number	: 1-800-424-9300 (CHEMTREC)
------------------	-----------------------------

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA/US)

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container; may burst if heated.
Serious eye damage/eye irritation, Category 2A	Causes serious eye irritation.
Germ cell mutagenicity, Category 1B	May cause genetic defects.
Carcinogenicity, Category 1B	May cause cancer.
Reproductive toxicity, Category 2	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.
Specific target organ toxicity, Repeated exposure, Category 1	Causes damage to organs through prolonged or repeated exposure.

#### 2.2. GHS label elements, including precautionary statements

##### GHS CA/US labeling

Hazard pictograms (GHS CA/US)



Signal word (GHS CA/US)

: Danger

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Hazard statements (GHS CA/US)	: Extremely flammable aerosol Pressurized container; may burst if heated Causes serious eye irritation May cause drowsiness or dizziness May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child Causes damage to organs through prolonged or repeated exposure.
Precautionary statements (GHS CA/US)	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Acetone	acetone, propan-2-one, propanone Dimethyl ketone / 2-Propanone / ACETONE / Propan-2-one / Propanone	CAS-No.: 67-64-1	65 - 85

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Name	Chemical name / Synonyms	Product identifier	%
Naphtha, petroleum, hydrotreated light	Naphtha (petroleum), hydrotreated light / Naphtha, petroleum, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4-11 and boiling in the range of approximately minus 20-190°C.) / Hydrocarbons, C7, n-alkanes, isoalkanes, cyclo	CAS-No.: 64742-49-0	5 - 10
Carbon dioxide	CARBON DIOXIDE / Dry ice / R-744	CAS-No.: 124-38-9	3 - 7
Toluene	Toluene Benzene, methyl- / Methylbenzene / Phenylmethane / TOLUENE	CAS-No.: 108-88-3	1 - 5
n-Heptane	heptane, n-heptane Heptane (n-) / Heptane / Normal heptane / Heptane, n- / HEPTANE	CAS-No.: 142-82-5	0.1 – 1

### Comments

: CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of December 2022.  
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	: Do not induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Prolonged inhalation may be harmful. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may dry skin and cause irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.
Chronic symptoms	: May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. Treat symptomatically.

## SECTION 5 Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.

Explosion hazard : Pressurized container: may burst if heated. No direct explosion hazard.

Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon.

### 5.3. Special protective actions for fire-fighters

Firefighting instructions : In case of fire: Stop leak if safe to do so. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : In the event of a significant spillage : Notify authorities if product enters sewers or public waters. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Pick up spilled material and collect it in a suitable container for disposal. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.

Other information : This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Do not breathe spray. Do not taste or swallow. Ensure good ventilation of the work station. Handle and open container with care.

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store this product upright in a cool, dry area, away from direct sunlight and heat. Store away from incompatible materials (see Section 10 of the SDS). Stored containers should be periodically checked for general condition and leakage. Store locked up.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

#### Acetone (67-64-1)

##### Canada (Alberta) - Occupational Exposure Limits

OEL TWA	1200 mg/m <sup>3</sup> 500 ppm
OEL STEL	1800 mg/m <sup>3</sup> 750 ppm
Regulatory reference	Alberta Regulation 191/2021

##### Canada (Quebec) - Occupational Exposure Limits

VECD (OEL STEV)	2380 mg/m <sup>3</sup> 1000 ppm
VEMP (OEL TWAEV)	1190 mg/m <sup>3</sup> 500 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

##### Canada (British Columbia) - Occupational Exposure Limits

OEL TWA	250 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

##### Canada (Manitoba) - Occupational Exposure Limits

OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025

##### Canada (New Brunswick) - Occupational Exposure Limits

OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	eye irr; CNS impair; BEI

##### Canada (Newfoundland and Labrador) - Occupational Exposure Limits

OEL TWA	250 ppm
---------	---------

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Acetone (67-64-1)</b>	
OEL STEL	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWAEV	250 ppm
	500 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Canada (Yukon) - Occupational Exposure Limits</b>	
OEL TWA	2400 mg/m <sup>3</sup>
	1000 ppm
OEL STEL	3000 mg/m <sup>3</sup>
	1250 ppm

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Acetone (67-64-1)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	250 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2025
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	Acetone
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	2400 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Carbon dioxide (124-38-9)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VECD (OEL STEV)	54000 mg/m <sup>3</sup>
	30000 ppm
VEMP (OEL TWAEV)	9000 mg/m <sup>3</sup>
	5000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	5000 ppm
OEL STEL	15000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Carbon dioxide (124-38-9)</b>	
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
OEL TWA	5000 ppm
OEL STEL	30000 ppm
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWAEV	5000 ppm
	30000 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Carbon dioxide (124-38-9)</b>	
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Canada (Yukon) - Occupational Exposure Limits</b>	
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	27000 mg/m <sup>3</sup>
	15000 ppm
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
ACGIH OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm
Remark (ACGIH)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Toluene (108-88-3)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	188 mg/m <sup>3</sup>
	50 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWAEV)	20 ppm
Notations and remarks	OTO
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
Notations and remarks	R (the substance has an adverse reproductive effect)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Toluene (108-88-3)</b>	
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
OEL TWA	50 ppm
OEL STEL	60 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
OEL TWA	50 ppm
OEL STEL	60 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWAEV	20 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	50 ppm
OEL STEL	60 ppm

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Toluene (108-88-3)</b>	
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Canada (Yukon) - Occupational Exposure Limits</b>	
OEL TWA	375 mg/m <sup>3</sup>
	100 ppm
OEL STEL	560 mg/m <sup>3</sup>
	150 ppm
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2025
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	Toluene
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	200 ppm
OSHA PEL C	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
<b>n-Heptane (142-82-5)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	1640 mg/m <sup>3</sup>
	400 ppm
OEL STEL	2050 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VECD (OEL STEV)	500 ppm
VEMP (OEL TWAEV)	400 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

### n-Heptane (142-82-5)

#### Canada (British Columbia) - Occupational Exposure Limits

OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

#### Canada (Manitoba) - Occupational Exposure Limits

OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025

#### Canada (New Brunswick) - Occupational Exposure Limits

OEL TWA	400 ppm
OEL STEL	500 ppm (Heptane, all isomers)

#### Canada (Newfoundland and Labrador) - Occupational Exposure Limits

OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025

#### Canada (Nova Scotia) - Occupational Exposure Limits

OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025

#### Canada (Nunavut) - Occupational Exposure Limits

OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)

#### Canada (Northwest Territories) - Occupational Exposure Limits

OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)

#### Canada (Ontario) - Occupational Exposure Limits

OEL TWAEV	400 ppm
	500 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833

#### Canada (Prince Edward Island) - Occupational Exposure Limits

OEL TWA	200 ppm
OEL STEL	400 ppm

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>n-Heptane (142-82-5)</b>	
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Canada (Yukon) - Occupational Exposure Limits</b>	
OEL TWA	1600 mg/m <sup>3</sup>
	400 ppm
OEL STEL	2000 mg/m <sup>3</sup>
	500 ppm
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	2000 mg/m <sup>3</sup>
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

### Naphtha, petroleum, hydrotreated light (64742-49-0)

#### Canada (Prince Edward Island) - Occupational Exposure Limits

OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

##### Hand protection:

Wear protective gloves. Confirm with a reputable supplier first.

##### Eye protection:

Wear safety glasses with side shields (or goggles).

##### Skin and body protection:

Wear suitable protective clothing. As required by employer code.

##### Respiratory protection:

Use respiratory protection. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

## SECTION 9 Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: No data available
Odor	: Sweet , Pungent
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 6.70609 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Oxidizing properties	: Not oxidising.
Explosion limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 9.5039 %
-------------	------------

## SECTION 10 Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: No flames, no sparks. Eliminate all sources of ignition. Do not mix with other chemicals.
Incompatible materials	: Strong oxidizing agents. Acids. Reducing agents. Caustic.
Hazardous decomposition products	: May include and are not limited to: oxides of carbon.

## SECTION 11 Toxicological information

### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Acetone (67-64-1)

LD50 oral rat	5800 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 15700 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	50100 mg/m³ (Exposure time: 8 h Source: OECD_SIDS)
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA
ATE CA (oral)	5800 mg/kg body weight
ATE CA (vapors)	50.1 mg/l/4h
ATE CA (dust,mist)	50.1 mg/l/4h

#### Toluene (108-88-3)

LC50 Inhalation - Rat	12.5 mg/l/4h
LC50 Inhalation - Rat (Vapors)	> 20 mg/l Source: ECHA

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Toluene (108-88-3)</b>	
ATE CA (Gases)	4500 ppmV/4h
ATE CA (vapors)	12.5 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
<b>n-Heptane (142-82-5)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)
LC50 Inhalation - Rat	> 73.5 mg/l/4h
ATE CA (Dermal)	3000 mg/kg body weight
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg (Source: IUCLID)
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm/4h
ATE CA (Dermal)	2800 mg/kg body weight
ATE CA (Gases)	73680 ppmV/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
<b>Toluene (108-88-3)</b>	
LOAEL (oral, rat, 90 days)	1250 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapor, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
<b>n-Heptane (142-82-5)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

### Naphtha, petroleum, hydrotreated light (64742-49-0)

NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
Aspiration hazard	: Not classified
Likely routes of exposure	: Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may dry skin and cause irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.
Chronic symptoms	: May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

### SECTION 12 Ecological information

#### 12.1. Toxicity

Ecology - general	: See below for route-specific details.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

### Acetone (67-64-1)

LC50 - Fish [1]	4.74 – 6.33 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### Toluene (108-88-3)

LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

### n-Heptane (142-82-5)

LC50 - Fish [1]	375 mg/l (Exposure time: 96 h - Species: Cichlid fish)
EC50 - Crustacea [1]	1.5 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>n-Heptane (142-82-5)</b>	
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LC50 - Fish [1]	8.41 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static, closed] Source: ECHA)
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

<b>Degreasing Solvent LV</b>	
Persistence and degradability	Rapidly degradable
<b>Acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
<b>Carbon dioxide (124-38-9)</b>	
Persistence and degradability	Rapidly degradable
<b>Toluene (108-88-3)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
<b>n-Heptane (142-82-5)</b>	
Persistence and degradability	Rapidly degradable
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

<b>Acetone (67-64-1)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	(0.69 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	-0.24
<b>Carbon dioxide (124-38-9)</b>	
BCF - Fish [1]	(no bioaccumulation)
<b>Toluene (108-88-3)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

<b>Toluene (108-88-3)</b>	
BCF - Fish [1]	90 (3 day(s), Leuciscus idus, Static renewal, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7))
<b>n-Heptane (142-82-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	4.66

### 12.4. Mobility in soil

<b>Acetone (67-64-1)</b>	
Surface tension	23.3 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
<b>Toluene (108-88-3)</b>	
Surface tension	27.73 mN/m (25 °C, 0.05 %)
Ecology - soil	Low potential for adsorption in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, Calculated value)

### 12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of the material collected according to regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection.

## SECTION 14 Transport information




In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
<b>14.1. UN Number</b>			
UN1950	UN1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>			
AEROSOLS	Aerosols	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>			
UN1950 AEROSOLS, 2.1	UN1950 Aerosols, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>			
LTD QTY	LTD QTY	LTD QTY	LTD QTY Y

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

TDG	DOT	IMDG	IATA
			
<b>14.4. Packing group, if applicable</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

### 14.6. Special precautions for user

#### TDG

UN-No. (TDG) : UN1950  
Excepted quantities (TDG) : E0  
Emergency Response Guide (ERG) Number : 126

#### DOT

UN-No. (DOT) : UN1950  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

#### IATA

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provision (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

### 14.7. Transport in bulk according to Annex II of MARPOL 73/789(^9) and the IBC Code(^10)

Not applicable

## SECTION 15 Regulatory information

All components of this product are present on DSL

### Carbon dioxide (124-38-9)

Toxic Substance (CEPA – Schedule I)	Yes
-------------------------------------	-----

### Benzene (71-43-2)

Toxic Substance (CEPA – Schedule I)	Yes
-------------------------------------	-----

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	1 - 5%
---------	------------------	--------

### Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

### Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

### Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

### Benzene (71-43-2)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	10 lb received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule
-----------	---

# Degreasing Solvent LV

## Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)



This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16 Other Information

Issue date : 09/09/2025

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

Prepared by: Nu-Calgon Technical Service Phone: (314) 469-7000.

The information in the safety data sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.