

4150-03

Nu-Calgon




PATENTED

- Installs in **SECONDS!**
- Made **STRONG**
- **REUSABLE!**
- **EASY** Install
- **10 FOOT** Drain Line
- **360°** Coverage
- Prevents Overspray\*

**Fits All Ceiling Cassette Types**

\*NOTE: The Clean Guard does not cover exposed electronics. Please be sure to protect any electronics when cleaning with a cleaner and when pressurized water is required.

**ANTIMICROBIAL TECHNOLOGY!**



**Clean Guard is treated to resist deterioration by mold fungus!**



Nu-Calgon  
2611 Schuetz Road | St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(0923) Calgon is a licensed trade name.

Made in Panama.

# Clean Guard™ CC

## Professional Cassette Maintenance Bag



**HEAVY DUTY**

Durable braided elastic band with wheel lock adjusts in seconds for a desired fit!



For Professional Use Only • Instructions On Back

## Directions For Use:

**This product must be used in accordance to following directions by HVACR professionals only.**

Ensure You Have Proper Supplies Before You Start: The Clean Guard CC (4150-03) is for cleaning of ceiling cassette systems. Other supplies required include Nu-Calgon coil cleaner, Turbo Tank pressure sprayer (or other market option) and five gallon bucket to collect the dispensed solution.

1. Disconnect power from the unit.
2. All ceiling cassettes come with a removable cover. When cleaning a cassette unit, remove the center air intake grill (or take the cover completely off) along with the motor and fan to access the coil and drain pan. If only the center grill is removed, the Clean Guard CC will attach to the lip of the outer cover since it sits below the drywall or drop ceiling. If the entire ceiling cassette cover is removed, the Clean Guard CC bag will attach to the unit flanges for the coil to be cleaned.
3. Simply open up the bag, center it on the mini-split and tighten adequately around the lip of outer ceiling cassette cover (if only center grill is removed) or cassette flange (if the outer ceiling cassette cover is removed). Tighten the elastic band with the wheel lock to where the bag hangs securely enough from the cassette unit and yet allows access for coil cleaning.
4. Position the five gallon bucket on a stable surface, typically the floor in most cases, and position the Clean Guard CC funnel into the bucket.
5. During cleaning, wear protective gloves and eyewear.
6. Select a Nu-Calgon coil cleaner that is best suited for the job. For coils and blowers that need to be cleaned and disinfected, choose Nu-Calgon's Evap-Fresh gallon (4166-08) with the use of 50P Sprayer (4770-0) or Evap-Fresh No Rinse aerosol (4166-75) with the use of the Talon Flexible Wand (4776-0). For tough duty, Tri-Pow'r HD aerosol coil cleaner (4371-75) is a good option.
7. Rinse with Nu-Calgon's Turbo Tank 2.0 (4781-00) or other readily available market option.
8. While cleaning, keep an eye on the five gallon bucket to cleaner/water is draining into bucket properly; resolve any kinks in the Clean Guard CC as necessary.
9. When done cleaning, while Clean Guard CC is still hanging independently on the ceiling cassette, briefly turn on unit to collect any remaining water droplets that could be discharged.
10. Remove Clean Guard CC and recommission the mini-split back to service.
11. Rinse, dry and store the Clean Guard CC inside the bucket for repeated use.

## Limited Warranty

Nu-Calgon warrants this item from defects in material and workmanship. Nu-Calgon will replace once proven upon examination to be defective. This warranty is valid for 30 days from date of the original purchase. This warranty excludes unusual wear, abuse, unreasonable use or damage from an accident. Contact your local Nu-Calgon authorized wholesaler for further assistance.

## Recommended Products

