

FOAM-BRITE'S EXPANDING FOAM IS GREAT FOR CLEANING:

- Greasy Deposits
- Cooking Grease
- Dirt and Grime
- Lint and Dust
- Oxide Deposits
- Cottonwood and Bugs

DILUTION RATIO – OUTDOOR COILS	
Heavy Duty	4:1
Medium Duty	6:1
Routine Maintenance	8:1

COIL GUN® SETTINGS	
Heavy Duty	Set Dial to B
Medium Duty	Set Dial to C
Routine Maintenance	Set Dial to D

Recommended to use Nu-Calgon's Coil Gun (4774-0)

DO NOT USE ON INDOOR COILS. NOT FOR INDOOR USE.

NOTE: For maximum results, do not use Foam-Brite undiluted or any stronger than 3:1 dilution ratio



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(0225) Calgon is a licensed trade name.

FEATURES: Foam-Brite® is an advanced cleaning solution engineered for outdoor HVACR coils. It provides the ultimate foaming action, allowing the cleaner to penetrate deeply into surfaces effectively lifting and removing dirt, grease, and grime. Foam-Brite is designed to clean a variety of soils off coil and formulated with hard water tolerance to maintain efficiency after dilution with any water source. Use Foam Brite to ensure coil is thoroughly cleaned and the unit is running in peak condition.

APPLICATIONS:

- Commercial HVACR systems
- Roof top units exposed to exhaust fan fumes
- Residential Condensers
- HVACR Maintenance Programs

NOTE: For painted fin or microchannel coils, use Tri-Pow'r®, Blackhawk®, Cal-Green™, or TriClean™ 2x.



DIRECTIONS: For use by HVACR professionals only:

- Turn off or disconnect unit power.
- Clear away heavy dirt.
- Wear goggles, gloves and other protective garments should be worn. Mix Foam-Brite cleaning solution according to dilution chart.
- Allow foam to expand from within the coil 5-10 minutes.
- Once the foam has lifted the grease and grime from within the coil, rinse thoroughly with water.
- Ensure cleaning solution is completely removed from coil.
- For heavy soils, repeat application.
- Return unit to operation.

4178-08

Nu-Calgon



Maximum Foaming Action
Excellent Degreasing Capability
Brightens and Shines



For Professional Use Only.
Keep Out Of Reach Of Children.

1 U.S. Gallon (3.8 Liters)

AFFECT ON ROOFING MATERIAL: Depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly galvanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated roofing surfaces

RUBBER ROOFS: In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use Tri-Pow'r, Cal-Green, Green Clean or CalClean - first evaluate in a small test area.



DANGER
Causes severe skin burns and eye damage.

PREVENTION: Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection.

RESPONSE: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. Specific treatment (see information on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

STORAGE: Store locked up.

DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations.

KEEP OUT OF REACH OF CHILDREN.

CONTAINS (CAS#): Water (7732-18-5), Sodium Hydroxide (1310-73-2), Carboxylate Sodium Salt (Proprietary), Plant Derived Surfactant (Proprietary), Plant Derived Surfactant (Proprietary), Colorant.