



Discover the performance of Fluorescent Gas Leak Detector, your go-to solution for detecting gas leaks with precision and efficiency. The unique formulation is non-corrosive and engineered to meet the needs of today's service technicians. Use Fluorescent Gas Leak Detector to ensure confidence when gas leak detection is required.

**FEATURES:**

- Long-Lasting Bubbles:** Extended bubble life ensuring reliable detection of gas leaks.
- Surface Adhesion:** High viscosity formulation clings to surfaces for superior contact time, enabling the detection of the smallest leaks in the system.
- Fluorescent Dye for Improved Visibility:** Increased visibility of bubbles in sunlight or bright light.
- Versatile Application:** Works with all refrigerants including A2L, natural gas, and oxygen.
- Freeze Protection:** Resistant to freezing at temperatures as low as 5°F and capable of withstanding temperatures up to 225°F
- Non-Corrosive, Biodegradable, and Freeze Thaw Stable:** The most advanced gas leak detection formula on the market!



4184-24



# Fluorescent Gas Leak Detector

MICRO LEAK DETECTOR



Fluorescent Dye For Easy Detection

Freeze Protected to 5°F

Detects Microscopic Leaks

For Professional Use Only.  
Keep Out Of Reach Of Children. 1 Quart/32 fl. oz. (946mL)



**DIRECTIONS:** For use by HVACR professionals only



**Prepare Surface:** Ensure the system is pressurized and all safety measures are in place.



**Application:** Liberally spray a uniform coating on surfaces suspected of leaks.



**Visual Inspection:** Look for signs of white foam or formation of small bubbles.



**Patience is Key:** Bubbles will form instantly in most applications. For micro leaks, allow 5 minutes for the solution to work.



**Check Fittings:** Inspect the bottom of all fittings for foam or small bubbles.



**Response to Leaks:** If a leak is detected, consider using Nu-Calgon's EasySeal if the situation is appropriate.



**Sprayer Tip:** Twist the sprayer tip to the off position when not in use.

**PREVENTION:** Observe good industrial hygiene practices.  
**RESPONSE:** Wash hands after handling.  
**STORAGE:** Store away from incompatible materials.  
**DISPOSAL:** Dispose of waste and residues in accordance with local authority requirements  
**KEEP OUT OF REACH OF CHILDREN**  
**CONTAINS:** Propylene Glycol (CAS# 57-55-6).



Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(925) Calgon is a licensed trade name.