

4305-07

 **Nu-Calgon**



PROVIDES EXCELLENT LUBRICATION

SUPERB STABILITY

LOW TEMPERATURE PERFORMANCE



For Professional Use Only.
Keep Out Of Reach Of Children.

1 U.S. Gallon (3.8 Liters)

APPLICATION:

Nu-Calgon Refrigeration Oils are recommended for use with all HCFC refrigerants.

FOLLOW THE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS. If none are available, use the following as a guide:

DIRECTIONS FOR USE:

1. For R22 and other HCFC refrigerants with evaporator temperatures above -20°F, use Nu-Calgon's C-3s or C-4s Refrigeration Oils. Below -20°F, use only C-3s Refrigeration Oil.
2. For R22 and other HCFC refrigerants, ethane, propane, and isobutane, use Nu-Calgon's C-3s Refrigeration Oil.
3. For ammonia with evaporator temperatures above -20°F use Nu-Calgon's C-4s or C-5s Refrigeration Oil. Below -20°F, use C-3s Refrigeration Oil.
4. When using "drop-in" refrigerants that call for a mineral oil, select one of the Nu-Calgon Refrigeration Oils in accordance with the appropriate viscosity required and evaporator temperatures.

CAUTION: Keep container tightly closed. Moisture in air will contaminate the oil.

CONTAINS: Distillates (petroleum), hydrotreated heavy naphthenic (CAS #64742-52-5).

KEEP OUT OF REACH OF CHILDREN.

MINERAL OIL	VISCOSITY AT 100°F
C-3s (Calumet R015)	150 SUS (ISO 32)
C-4s (Calumet R030)	300 SUS (ISO 68)
C-5s (Calumet R050)	500 SUS (ISO 100)

Manufactured by: Calumet, Inc.



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(1024) Calgon is a licensed trade name.