




4623-11

Nu-Calgon



### DIRECTIONS



Replace cartridge annually or sooner, should flow become less than desirable.

### SPECIFICATIONS

Filters For:	6 months
Dimensions:	12.25" x 3.39" (31.12cm x 8.61cm)
Operating Pressure:	25-125 psi (0.7-8.6 bar)
Operating Temperature:	40-100°F (2-38°C)
Maximum Service Flow Rate:	1.67 gpm (6.32 lpm)

Nu-Calgon  
2611 Schuetz Rd. • St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
Calgon is a licensed trade name. (0824)

4623-11

Nu-Calgon



5 Micron Sediment Reduction  
Scale Inhibitor

Replaces 3M™/CUNO™  
CFS8110-S

Ice/Coffee/Tea/Steam

Use with Nu-Plus CFS  
or OEM manifolds

**DATE OF INSTALL:**

4623-11

Nu-Calgon



### NOTES

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- Meets or exceeds the performance of the cross-referenced 3M™/CUNO™ product listed.
- Tested by the manufacturer to ANSI/NSF Standard 42 for material requirements only.
- Cartridge capacity may vary according to flow rate, inlet line pressure and local water conditions, which may require more frequent cartridge replacement.
- Install on cold water line only.



CUNO™ is a trademark of 3M. This product is not manufactured, sponsored or affiliated with 3M.