

1. Product and Company Identification

| | | |
|--------------------------------------|--|--|
| Product identifier | pH-Treat Condensate Neutralization Media (4720-08, 4720-10, 4720-11, 4720-12, 4720-13) | |
| Other means of identification | Not available | |
| Recommended use | For use in Condensate Neutralizers | |
| Recommended restrictions | None known. | |
| Manufacturer information | Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC) | |
| Supplier | See above. | |

2. Hazards Identification

| | | |
|-----------------------------------|-----------------------------------|------------|
| Physical hazards | Not classified. | |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2 |
| Environmental hazards | Not classified. | |
| WHMIS 2015 defined hazards | Not classified | |
| Label elements | | |



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear protective gloves. Wear eye protection.

Response IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/Information on Ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------|--------------------------|------------|---------|
| Aluminum oxide | | 1344-28-1 | 1-5* |
| Calcium oxide | | 1305-78-8 | 1-5* |
| Ferric oxide | | 1309-37-1 | 1-5* |
| Magnesium oxide | | 1309-48-4 | 80-100* |
| Silica | | 7631-86-9 | 5-10* |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

| | |
|---|--|
| Inhalation | If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention. |
| Skin contact | IF ON SKIN: Wash with plenty of soap and water. Specific treatment (see information on this label). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. |
| Eye contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Ingestion | Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention. |
| Most important symptoms/effects, acute and delayed | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. |
| General information | If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. |

5. Fire Fighting Measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire-fighting equipment/instructions | Use water spray to cool unopened containers. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |
| Hazardous combustion products | May include and are not limited to: Oxides of carbon. Oxides of magnesium. |

6. Accidental Release Measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | The product is immiscible with water and will spread on the water surface. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| Environmental precautions | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters. |

7. Handling and Storage

| | |
|--------------------------------------|---|
| Precautions for safe handling | Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink. |
|--------------------------------------|---|

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store in a cool, dry, well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Store between 10°C - 30°C. Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Type | Value | Form |
|---------------------------------|------|----------|-------------|
| Aluminum oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | |
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Fume. |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value | Form |
|---------------------------------|------|-----------|------------------------------|
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | STEL | 10 mg/m3 | Fume. |
| | TWA | 5 mg/m3 | Dust. |
| | | 5 mg/m3 | Fume. |
| | | 3 mg/m3 | Respirable fraction. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Total dust. |
| | STEL | 10 mg/m3 | Respirable dust and/or fume. |
| | TWA | 3 mg/m3 | Respirable dust and/or fume. |
| | | 10 mg/m3 | Inhalable fume. |
| Silica (CAS 7631-86-9) | TWA | 4 mg/m3 | Total |
| | | 1.5 mg/m3 | Respirable. |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Aluminum oxide (CAS 1344-28-1) | TWA | 1 mg/m3 | Respirable fraction. |
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Inhalable fraction. |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Inhalable fraction. |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value | Form |
|--------------------------------|------|----------|----------------|
| Aluminum oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | Total dust. |
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Dust and fume. |
| | | 10 mg/m3 | Total dust. |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value | Form |
|---------------------------------|------|----------|------------------|
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Fume. |
| Silica (CAS 7631-86-9) | TWA | 6 mg/m3 | Respirable dust. |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Aluminum oxide (CAS 1344-28-1) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| Calcium oxide (CAS 1305-78-8) | PEL | 5 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | PEL | 10 mg/m3 | Fume. |
| Magnesium oxide (CAS 1309-48-4) | PEL | 15 mg/m3 | Total particulate. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---------------------------------|------|-----------|----------------------|
| Aluminum oxide (CAS 1344-28-1) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |
| Silica (CAS 7631-86-9) | TWA | 0.8 mg/m3 | |
| | | 20 mppcf | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Aluminum oxide (CAS 1344-28-1) | TWA | 1 mg/m3 | Respirable fraction. |
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| Magnesium oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Inhalable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|-------------------------------|------|---------|----------------|
| Calcium oxide (CAS 1305-78-8) | TWA | 2 mg/m3 | |
| Ferric oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Dust and fume. |
| Silica (CAS 7631-86-9) | TWA | 6 mg/m3 | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

| | |
|---------------------------------------|--|
| Skin protection | |
| Hand protection | Impervious gloves. Confirm with reputable supplier first. |
| Other | Wear appropriate chemical resistant clothing. As required by employer code. |
| Respiratory protection | Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). |
| Thermal hazards | Not applicable. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink. |

9. Physical and Chemical Properties

| | |
|---|-----------------------|
| Appearance | Spheres |
| Physical state | Solid. |
| Form | Solid. |
| Color | White |
| Odor | Odorless |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | > 4046 °F (> 2230 °C) |
| Pour point | Not available. |
| Specific gravity | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Flash point | None |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | Insoluble |
| Auto-ignition temperature | > 698 °F (> 370 °C) |
| Decomposition temperature | Not available. |
| Viscosity | Not applicable |
| Other information | |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

10. Stability and Reactivity

| | |
|---|---|
| Reactivity | This product may react with strong oxidizing agents. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Chemical stability | Material is stable under normal conditions. |
| Conditions to avoid | Do not mix with other chemicals. |
| Incompatible materials | Phosphorus pentachloride. Chlorine trifluoride. Bromine pentafluoride. Acids. Halogens. |
| Hazardous decomposition products | No hazardous decomposition products are known. May include and are not limited to: |

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion May cause stomach distress, nausea or vomiting.

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results |
|---------------------------------|---------------|--|
| Aluminum oxide (CAS 1344-28-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 10 mg/L, 4 Hours, ECHA > 2.3 mg/L, 4 Hours, ECHA > 0.9 mg/L, 4 Hours, ECHA 7.6 mg/L, 1 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | > 15900 mg/kg, ECHA > 15900 mg/kg, 14 days, ECHA > 10000 mg/kg, Sigma Aldrich > 2000 mg/kg, ECHA 5000 mg/kg, EMD Millipore |
| Calcium oxide (CAS 1305-78-8) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 2500 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 6 mg/m ³ , 4 hours, ECHA |
| <i>Oral</i> | | |
| LD50 | Rat | > 2000 mg/kg, ECHA 790 mg/kg |
| Ferric oxide (CAS 1309-37-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 5 mg/l/4h, ECHA |
| <i>Oral</i> | | |
| LD50 | Rat | > 5000 mg/kg, ECHA |
| Magnesium oxide (CAS 1309-48-4) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Not available | |

| Components | Species | Test Results |
|---|--|---|
| Oral LD50 | Rat | 3990 mg/kg, Canada Colors |
| Silica (CAS 7631-86-9) | | |
| Acute | | |
| Dermal LD50 | Rabbit | > 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA |
| Inhalation LC50 | Rat | > 58.8 mg/L, 4 Hours, ECHA > 2.1 mg/L, 4 Hours, ECHA > 0.7 mg/L, 4 Hours > 0.1 mg/L, 4 Hours, ECHA |
| Oral LD50 | Rat | > 5000 mg/kg, ECHA |
| Skin corrosion/irritation | Causes skin irritation. | |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |
| Conjunctival oedema value | Not available. | |
| Recover days | Not available. | |
| Respiratory or skin sensitization | | |
| Canada - Alberta OELs: Irritant | | |
| Calcium oxide (CAS 1305-78-8) | | Irritant |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | See below. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Ferric oxide (CAS 1309-37-1) | | Volume 1, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans. |
| Silica (CAS 7631-86-9) | | Volume 68 - 3 Not classifiable as to carcinogenicity to humans. |
| US - California Proposition 65 - CRT: Listed date/Carcinogenic substance | | |
| Crystalline silica (CAS 14808-60-7) | | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Teratogenicity | Not available. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not an aspiration hazard. | |
| Chronic effects | Prolonged inhalation may be harmful. | |

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data**Components**

Silica (CAS 7631-86-9)

Algae

IC50

Species

Algae

Test Results

440 mg/L, 72 Hours

Crustacea

EC50

Daphnia

7600 mg/L, 48 Hours

Persistence and degradability No data is available on the degradability of this product.**Bioaccumulative potential** No data available.**Mobility in soil** No data available.**Mobility in general** Not available.**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.**U.S. Department of Transportation (DOT)**

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.**Canada CEPA Schedule I: Listed substance**

Aluminum oxide (CAS 1344-28-1)

Listed.

Ferric oxide (CAS 1309-37-1)

Listed.

Magnesium oxide (CAS 1309-48-4)

Listed.

Canada Priority Substances List (Second List): Listed substance

Aluminum oxide (CAS 1344-28-1)

Listed.

Ferric oxide (CAS 1309-37-1)

Listed.

Magnesium oxide (CAS 1309-48-4)

Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All chemicals used are on the TSCA inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|----------------------|-------------------|-----------------|
| Aluminum oxide | 1344-28-1 | 1-5* |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Aluminum oxide (CAS 1344-28-1) Listed.
Calcium oxide (CAS 1305-78-8) Listed.
Ferric oxide (CAS 1309-37-1) Listed.
Magnesium oxide (CAS 1309-48-4) Listed.
Silica (CAS 7631-86-9) Listed.

US - Minnesota Haz Subs: Listed substance

Aluminum oxide (CAS 1344-28-1) Listed.
Calcium oxide (CAS 1305-78-8) Listed.
Ferric oxide (CAS 1309-37-1) Listed.
Magnesium oxide (CAS 1309-48-4) Listed.
Silica (CAS 7631-86-9) Listed.

US - New Jersey RTK - Substances: Listed substance

Aluminum oxide (CAS 1344-28-1)
Calcium oxide (CAS 1305-78-8)
Ferric oxide (CAS 1309-37-1)
Magnesium oxide (CAS 1309-48-4)
Silica (CAS 7631-86-9)

US - Texas Effects Screening Levels: Listed substance

Aluminum oxide (CAS 1344-28-1) Listed.
Calcium oxide (CAS 1305-78-8) Listed.
Ferric oxide (CAS 1309-37-1) Listed.
Magnesium oxide (CAS 1309-48-4) Listed.
Silica (CAS 7631-86-9) Listed.

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)
Calcium oxide (CAS 1305-78-8)
Ferric oxide (CAS 1309-37-1)
Magnesium oxide (CAS 1309-48-4)
Silica (CAS 7631-86-9)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum oxide (CAS 1344-28-1)
Calcium oxide (CAS 1305-78-8)
Ferric oxide (CAS 1309-37-1)
Magnesium oxide (CAS 1309-48-4)
Silica (CAS 7631-86-9)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)

Calcium oxide (CAS 1305-78-8)
Ferric oxide (CAS 1309-37-1)
Magnesium oxide (CAS 1309-48-4)

US. California Proposition 65



WARNING: This product can expose you to Silica, crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7) Listed: October 1, 1988

Inventory status


| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

| LEGEND | |
|----------|---|
| Severe | 4 |
| Serious | 3 |
| Moderate | 2 |
| Slight | 1 |
| Minimal | 0 |

| | |
|---------------------|-----|
| HEALTH | / 2 |
| FLAMMABILITY | 0 |
| PHYSICAL HAZARD | 0 |
| PERSONAL PROTECTION | X |



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

04-September-2022

Version #

0

Effective date

04-September-2022

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.