

7 45310 02009 5



PK-12 PC GHS 61040



1 410Y07

800-554-5499 • www.nucalgon.com • (0325)
2611 Schuetz Rd. • St. Louis, MO 63043



WARNING
Harmful if swallowed, harmful in contact with skin.

RESPONSE: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Rinse skin with water/shower. IF INHALED: Remove victim to fresh air. IF SWALLOWED: Immediately call a doctor/physician. Rinse mouth. Do NOT induce vomiting.

DISPOSAL: Dispose of contents/container to an approved waste disposal plant.

KEEP OUT OF REACH OF CHILDREN

The PurCool Pan Strip should be cut no smaller than 1" in length.

For systems under 30 tons, the PurCool Pan strip can be cut to size for treatment in smaller systems.

4. Replace the PurCool Pan Strip after 4-6 months.

3. Place the PurCool Pan Strip in the condensate drain pan so that it sits flat on the bottom of the pan. achieve maximum contact with the condensate.

2a. The PurCool Pan Strip should be away from the drain line opening and in a location where it will

2. Locate proper placement for the PurCool Pan Strip within the condensate pan.

1. Remove the yellow PurCool Pan Strip from the package.

to clear the clog before placing in the PurCool Pan Strip.

If the pan is noticeably clogged, first use the Nu-Calgon Gallo Gun

For use by HVACR professionals.



- Dissolves Completely
- Safe for Metal and Plastic Drain Pans
- Can be Cut for Lower Tonnage Units
- Improves Indoor Air Quality



- Prevents Condensate Pan Overflows
- Maintains Free Flowing Drains
- Lasts Up to 6 Months
- Eliminates Drain Pan Odors

61040
30 Ton



Prevents A/C Drain Pan Overflows

30 Ton Tablet Treats for 6 Months

**Prevents Sludge Build-Up • Cleans Drain Pan & Lines
Controls Odors**