

**Directions:**  
**This product must be used in accordance to the following directions by HVAC professionals.**


1. Open the top of the box and remove the plastic wrapped HVAC Odor Block.
2. Remove the HVAC Odor Block from the protective bag and place the HVAC Odor Block back in the box.
3. Hang or place the HVAC Odor Block in the HVAC system after the air filter or near blower compartment. A secondary location can be before the air filter.
4. Replace the HVAC Odor Block after 2 months.

**For larger systems, use HVAC Odor Block XL #6107-00**

**KEEP OUT OF REACH OF CHILDREN**  
 Do not store in temps below 40°F or above 120°F.

Contains fragrance allergen.  
 For more ingredient information visit [www.nucalgon.com](http://www.nucalgon.com). 800-554-5499

2611 Schuetz Rd. • St. Louis, MO 63043  
 Customer Service: 800-554-5499  
 Chemical Emergency: 800-424-9300  
[www.nucalgon.com](http://www.nucalgon.com)  
 (0124) Calgon is a licensed trade name.



**Nu-Calgon**



**ODOR REMOVAL**  
 Our product is a true odor neutralizer that removes odors from the air.

**LONG LASTING**  
 Enjoy up to 2 months of fresh fragrance with the HVAC Odor Block.

**SAFE AND EFFECTIVE**  
 For use in all applications and is an environmentally friendly formula.



**6106-00**

**Nu-Calgon**



**ODOR NEUTRALIZER**

- Eliminates odors in the HVAC system
- A true odor neutralizer, not a cover-up
- Freshens air through the HVAC system
  - Treats up to a 3 ton HVAC system
  - Lasts up to 2 months

FOR PROFESSIONAL USE ONLY

**Net Wt. 2 lb.**

Use the HVAC Odor Block in A/C units, furnaces, rooftop units, and air handlers.



The image above shows two locations for installation of the HVAC Odor Block

- The ideal location is after the air filter
- The secondary location is before the air filter

