

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : EasySeal Ultimate-LS/UV
Product code : 4050-11, 4050-12

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant leak sealant

1.4. Supplier's details

Manufacturer

Nu-Calgon
2611 Schuetz Road
St. Louis, MO
63043
US
T 314-469-7000 / 800-554-5499
www.nucalgon.com

1.5. Emergency phone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Flammable liquids, Category 3	Flammable liquid and vapor.
Skin corrosion/irritation, Category 1B	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	Causes serious eye damage.
Skin sensitization, Category 1	May cause an allergic skin reaction.
Health hazards not otherwise classified, Category 1	Causes severe damage to the respiratory tract.

2.2. GHS label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US) :



Signal word (GHS CA/US) : Danger

Hazard statements (GHS CA/US) : Flammable liquid and vapor
Causes severe skin burns and eye damage
May cause an allergic skin reaction
Causes severe damage to the respiratory tract

Precautionary statements (GHS CA/US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Ground and bond container and receiving equipment.
Use explosion-proof equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe vapors, mist.
Wash hands, forearms and face thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
Wash contaminated clothing before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or a doctor.
Specific treatment (see supplemental first aid instruction on this label).
In case of fire: Use appropriate media to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)-	2-Butyl-6-(butylamino)-1H-benz[de]isoquinoline-1,3(2H)-dione / Solvent Yellow 43 / 4-Butylamino-N-butyl-1,8-naphthalimide / Solvent Yellow 116	CAS-No.: 19125-99-6	15 - 40
1-Propanamine, 3-(triethoxysilyl)-	3-aminopropyltriethoxysilane / 3-Aminopropyltriethoxysilane / Propylamine, 3-(triethoxysilyl)- / Triethoxysilane, 3-aminopropyl- / .gamma.-Aminopropyltriethoxysilane / 3-(Triethoxysilyl)-1-propylamine / 3-(Triethoxysilyl)propylamine / AMINOPROPYL TRIETHOXYSILANE / 3-(Triethoxysilyl)propan-1-amine / (3-Aminopropyl)triethoxysilane / 1-Propylamine, 3-(triethoxysilyl)-	CAS-No.: 919-30-2	10 - 30

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Name	Chemical name / Synonyms	Product identifier	%
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	Butan-2-one O,O',O''-(methylsilylidyne)trioxime / Silane, methyltris(2-butanone oxime)- / 2-Butanone, O,O',O''-(methylsilylidyne)trioxine / Methyltris(1-methylpropylideneaminoxy)silane / 2-Butanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime] / Methyltri(ethylmethylketoxime)silane / Methyltri(ethylmethylketoxime)silane / Methyltri(butanoneoxime)silane	CAS-No.: 22984-54-9	10 - 30

Comments : CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of December 2022.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor.

First-aid measures after skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person.

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Causes severe damage to the respiratory tract.

Symptoms/effects after skin contact : Causes severe skin burns. May produce skin irritation, blistering, ulcers, and deep scarring. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically. Symptoms may be delayed.

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical powder. Water fog.

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon. Nitrogen oxides.

5.3. Special protective actions for fire-fighters

Firefighting instructions : In case of fire: Stop leak if safe to do so. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In the event of a significant spillage : Notify authorities if product enters sewers or public waters. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Notify authorities if product enters sewers or public waters. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.
Other information : Dispose of materials or solid residues at an authorized site. This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors, mist. Do not taste or swallow. Ensure good ventilation of the work station. Handle and open container with care.
Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Keep out of reach of children. Store tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Store locked up.
Storage area : Store away from heat.

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Chemical goggles or face shield with safety glasses

Skin and body protection:

Wear appropriate chemical resistant clothing.

Respiratory protection:

Use respiratory protection. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : No data available
Color : Yellow
Odor : No data available
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 86 °F Closed cup: > 30.0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive.
Oxidizing properties	: Not oxidising.
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: Flammable liquid and vapor.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. No flames, no sparks. Eliminate all sources of ignition. Do not mix with other chemicals.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: May include and are not limited to: oxides of carbon. Nitrogen oxides.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1-Propanamine, 3-(triethoxysilyl)- (919-30-2)	
LD50 oral rat	1780 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	4290 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat [ppm]	> 5 ppm (Exposure time: 6 h Source: ECHA_API)
ATE CA (oral)	1780 mg/kg body weight
ATE CA (Dermal)	4290 mg/kg body weight
2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)- (19125-99-6)	
NOAEL (oral,rat,90 days)	994 mg/kg body weight Animal: rat, Guideline: other:
1-Propanamine, 3-(triethoxysilyl)- (919-30-2)	
LOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEL (dermal,rat/rabbit,90 days)	17 mg/kg body weight Animal: rabbit
NOAEL (oral,rat,90 days)	200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

Likely routes of exposure : Skin and eye contact. Ingestion. Inhalation.

Symptoms/effects after inhalation : Causes severe damage to the respiratory tract.

Symptoms/effects after skin contact : Causes severe skin burns. May produce skin irritation, blistering, ulcers, and deep scarring. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : See below for route-specific details.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)- (19125-99-6)	
LC50 - Fish [1]	172.2475 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0.17 mg/l Test organisms (species): Daphnia magna
1-Propanamine, 3-(triethoxysilyl)- (919-30-2)	
LC50 - Fish [1]	> 934 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
EC50 - Crustacea [1]	331 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

EasySeal Ultimate-LS/UV	
Persistence and degradability	Rapidly degradable
1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)- (19125-99-6)	
Persistence and degradability	Rapidly degradable
1-Propanamine, 3-(triethoxysilyl)- (919-30-2)	
Persistence and degradability	Rapidly degradable
2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9)	
Persistence and degradability	Rapidly degradable

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

12.3. Bioaccumulative potential

1H-Benz[de]isoquinoline-1,3(2H)-dione, 2-butyl-6-(butylamino)- (19125-99-6)	
Partition coefficient n-octanol/water (Log Pow)	4.643 (at 25 °C)
1-Propanamine, 3-(triethoxysilyl)- (919-30-2)	
BCF - Fish [1]	(3.4 dimensionless (whole body w.w.))

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of the material collected according to regulations.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
UN2920	UN2920	2920	2920
14.2. UN Proper Shipping Name			
CORROSIVE LIQUID, FLAMMABLE, N.O.S. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-	Corrosive liquids, flammable, n.o.s. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-	CORROSIVE LIQUID, FLAMMABLE, N.O.S. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-	Corrosive liquid, flammable, n.o.s. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-
Transport document description			
UN2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-, 8 (3), II	UN2920 Corrosive liquids, flammable, n.o.s. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-, 8 (3), II	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-, 8 (3), II	UN 2920 Corrosive liquid, flammable, n.o.s. 1-Propanamine, 3-(triethoxysilyl)-, Silane, methyltriethoxy-, 8 (3+), II
14.3. Transport hazard class(es)			
LTD QTY	LTD QTY	LTD QTY	LTD QTY Y

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

TDG	DOT	IMDG	IATA

14.4. Packing group, if applicable

II	II	II	II
----	----	----	----

14.5. Environmental hazards

Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
-----------------------------------	-----------------------------------	---	-----------------------------------

No supplementary information available

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN2920
 Excepted quantities (TDG) : E2
 Emergency Response Guide (ERG) Number : 132

DOT

UN-No. (DOT) : UN2920
 DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
 T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
 TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: by the degree of filling formula. Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: for the mean coefficient of cubical expansion of the liquid. Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
 TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
 DOT Packaging Bulk (49 CFR 173.xxx) : 243
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
 DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.
 DOT Vessel Stowage Other : 25 - Shade from radiant heat, 40 - Stow "clear of living quarters"

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

IMDG

Special provision (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS
Stowage category (IMDG)	: C
Stowage and handling (IMDG)	: SW1, SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
ERG code (IATA)	: 8F

14.7. Transport in bulk according to Annex II of MARPOL 73/789(^9) and the IBC Code(^10)

Not applicable

SECTION 15 Regulatory information

All components of this product are present on DSL

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other Information

Issue date : 02/24/2026

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

Prepared by: Nu-Calgon Technical Service Phone: (314) 469-7000.

EasySeal Ultimate-LS/UV

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

The information in the safety data sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.