

SECTION 1 Identification

1.1. GHS Product identifier

Product name : Blackhawk
Product code : 4127-08

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coil Cleaner

1.4. Supplier's details

Manufacturer

Nu-Calgon
2611 Schuetz Road
St. Louis, MO
63043
US
T 314-469-7000 / 800-554-5499
www.nucalgon.com

1.5. Emergency phone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Skin corrosion/irritation, Category 2

Causes skin irritation.

Serious eye damage/eye irritation, Category 1

Causes serious eye damage.

2.2. GHS label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US)



Signal word (GHS CA/US)

: Danger

Hazard statements (GHS CA/US)

: Causes skin irritation
Causes serious eye damage

Precautionary statements (GHS CA/US)

: Wash hands, forearms and face thoroughly after handling.
Wear protective gloves, protective clothing, eye protection, face protection.
IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice or attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Immediately call a POISON CENTER or a doctor.

Specific treatment (see supplemental first aid instruction on this label).

Supplementary information

: No additional information available

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Sodium xylenesulfonate	Dimethylbenzenesulfonic acid, sodium salt / Benzenesulfonic acid, dimethyl-, sodium salt (1:1) / Xylenesulfonic acid, sodium salt	CAS-No.: 1300-72-7	1 - 5
Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy-	Polyoxyethylene monoundecyl ether / Undecan-1-ol, ethoxylated / Polyethylene glycol undecyl ether	CAS-No.: 34398-01-1	1 - 5
Tetrasodium EDTA	tetrasodium ethylene diamine tetraacetate Ethylenediaminetetraacetic acid, tetrasodium salt / Tetrasodium ethylenediaminetetraacetate / Acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	CAS-No.: 64-02-8	0.5 - 5
Sodium hydroxide	sodium hydroxide, caustic soda Caustic soda / Sodium hydroxide	CAS-No.: 1310-73-2	0.1 - 1

Comments

: CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of December 2022.

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
First-aid measures after ingestion	: Do not induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. Treat symptomatically.
-----------------------------------	---

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Treat for surrounding material.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard	: During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: May include and are not limited to: Oxides of carbon.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: In case of fire: Stop leak if safe to do so. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In the event of a significant spillage : Notify authorities if product enters sewers or public waters. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.
Other information	: This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Avoid breathing vapors, mist. Do not taste or swallow. Wear personal protective equipment. Ensure good ventilation of the work station. Handle and open container with care.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of reach of children. Store tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Sodium hydroxide (1310-73-2)	
Canada (Alberta) - Occupational Exposure Limits	
OEL C	2 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Plafond (OEL C)	2 mg/m ³
Notations and remarks	RP
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL C	2 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL C	2 mg/m ³
Notations and remarks	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
OEL C	2 mg/m ³
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL C	2 mg/m ³
Notations and remarks	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL C	2 mg/m ³

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Sodium hydroxide (1310-73-2)	
Notations and remarks	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
OEL C	2 mg/m³
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL C	2 mg/m³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
OEL C	2 mg/m³
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL C	2 mg/m³
Notations and remarks	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL C	2 mg/m³
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL C	2 mg/m³
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® C	2 mg/m³
Remark (ACGIH®)	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	2 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection:
Wear suitable gloves resistant to chemical penetration

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing. As required by employer code.

Respiratory protection:

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: 12
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 8.62 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive.
Oxidizing properties	: Not oxidising.
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: Reacts violently with strong acids. This product may react with strong oxidizing agents.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Keep away from heat and direct sunlight. Do not mix with other chemicals.
Incompatible materials	: Strong oxidizing agents. Acids.

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Hazardous decomposition products : May include and are not limited to: Oxides of carbon.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Tetrasodium EDTA (64-02-8)	
LD50 oral rat	1658 mg/kg (Source: Health Canada Hazardous Substance Assessment)
LC50 Inhalation - Rat [ppm]	24.3 ppm ECHA
ATE CA (oral)	1658 mg/kg body weight
ATE CA (Gases)	24.3 ppmV/4h

Sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	> 16.2 g/kg (Source: ECHA_API)
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 6.41 mg/l (Equivalent or similar to OECD 403, 232 minutes, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE CA (oral)	1000 mg/kg body weight

Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy- (34398-01-1)	
ATE CA (oral)	500 mg/kg body weight

Sodium hydroxide (1310-73-2)	
LD50 oral rat	325 mg/kg (Source: OECD_SIDIS)
LD50 dermal rabbit	1350 mg/kg (Source: NLM_HSDB)
ATE CA (oral)	325 mg/kg body weight
ATE CA (Dermal)	1350 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
pH: 12
Serious eye damage/irritation : Causes serious eye damage.
pH: 12
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Sodium xylenesulfonate (1300-72-7)	
NOAEL (chronic,oral,animal/female,2 years)	≥ 60 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Tetrasodium EDTA (64-02-8)	
LOAEL (oral,rat,90 days)	60 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Tetrasodium EDTA (64-02-8)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Animal sex: female, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	6 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Sodium xylenesulfonate (1300-72-7)	
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

Aspiration hazard	: Not classified
Likely routes of exposure	: Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general	: See below for route-specific details.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Tetrasodium EDTA (64-02-8)	
LC50 - Fish [1]	41 mg/l (Exposure time: 96 h - Species: <i>Lepomis macrochirus</i> [static] Source: IUCLID)
LC50 - Fish [2]	59.8 mg/l (Exposure time: 96 h - Species: <i>Pimephales promelas</i> [static] Source: IUCLID)
EC50 - Crustacea [1]	> 114 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	> 60 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>)
NOEC chronic fish	≥ 25.7 mg/l Test organisms (species): Duration: '35 d'
LOEC (chronic)	50 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'

Sodium xylenesulfonate (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, <i>Oncorhynchus mykiss</i> , Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value)
EC50 96h - Algae [1]	≥ 230 mg/l (EPA OTS 797.1050, <i>Selenastrum capricornutum</i> , Static system, Fresh water, Experimental value)

Sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	45.4 mg/l (Exposure time: 96 h - Species: <i>Oncorhynchus mykiss</i> [static] Source: IUCLID)
EC50 - Crustacea [1]	40 mg/l (48 h, <i>Ceriodaphnia</i> sp., Experimental value, Locomotor effect)

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

12.2. Persistence and degradability

Blackhawk

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Tetrasodium EDTA (64-02-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Sodium xylenesulfonate (1300-72-7)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy- (34398-01-1)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Sodium hydroxide (1310-73-2)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

Chemical oxygen demand (COD)	Not applicable (inorganic)
------------------------------	----------------------------

ThOD	Not applicable (inorganic)
------	----------------------------

12.3. Bioaccumulative potential

Sodium xylenesulfonate (1300-72-7)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

Partition coefficient n-octanol/water (Log Pow)	-3.12 (at 20 °C (at pH 11.96)
---	-------------------------------

Sodium hydroxide (1310-73-2)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

12.4. Mobility in soil

Sodium xylenesulfonate (1300-72-7)

Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
-----------------	---

Ecology - soil	Highly mobile in soil.
----------------	------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.42 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	---

Sodium hydroxide (1310-73-2)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of the material collected according to regulations.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG
Not regulated

DOT
Not regulated

IMDG
Not regulated

IATA
Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/789(^9) and the IBC Code(^10)

Not applicable

SECTION 15 Regulatory information

All components of this product are present on DSL

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Blackhawk

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)

Sodium hydroxide (1310-73-2)	
CERCLA RQ	1000 lb

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Sodium hydroxide(1310-73-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Trisodium nitrilotriacetate(5064-31-3)	U.S. - Massachusetts - Right To Know List
Sodium sulfate(7757-82-6)	U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16 Other Information

Issue date : 07/21/2026

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

. Prepared by: Nu-Calgon Technical Service Phone: (314) 469-7000.

The information in the safety data sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.