

4188-17

 Nu-Calgon

Freez-Kontr'l[®] 50

INHIBITED 50%
PROPYLENE GLYCOL

Freez-Kontr'l 50 is a complete premix heat transfer fluid formulated with 50% inhibited propylene glycol that provides corrosion protection plus freeze protection to -25°F. The blue dyed product is non-corrosive and provides freeze and corrosion protection for hydronic, snow melt, refrigeration or other closed loop systems. Safe for use where incidental contact with food or potable water could occur.

DIRECTIONS FOR USE:

This product must be used in accordance with the following directions by HVACR professionals only.

1. Clean fouled closed loop system with Nu-Calgon System Cleaner, Eco-Lyme[®] or Liquid Scale Dissolver followed by clean water flush before adding Freez-Kontr'l 50 into the system.
2. Determine if freeze or burst protection is required. Use freeze protection requirements is solution will be circulating by a pump. Freez-Kontr'l 50 provides -25°F freeze point or -95°F burst requirement.
3. Determine system volume and fill closed loop system with Freez-Kontr'l 50. Freez-Kontr'l 50 is a premix formulation.

Notes: For loops that utilize galvanized steel or CPVC materials, contact Nu-Calgon. Do not use Freez-Kontr'l 50 for open loop systems. This formulation is intended to be used as a ready-to-use. If diluted with water, never dilute beyond two parts Freez-Kontr'l 50 : one part water or below 30% propylene glycol solution in the system.

Always use a Nu-Calgon Glycol Refractometer (63101) to check freeze protection of the heat transfer fluid before leaving job site.

CONTAINS: Propylene Glycol (CAS No. 57-55-6).
DO NOT STORE PAIL IN DIRECT SUNLIGHT.
Consult SDS before use.



Nonfood Compounds
HT1



For Professional Use Only.
Keep Out Of Reach Of Children.

5 U.S. Gallons (18.9 Liters)

BO

LOT #



00681001001526

Nu-Calgon
2611 Schuetz Rd. | St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(0924) Calgon is a licensed trade name.