

BODY BLANK 8.150

Color Limits 7.900"

Type Limits 7.700"

SONOCO METAL PACKAGING
211 X 713 CONO II N.I.

22-0000

.094

.500

4369-75



Spray-N-Bond™
INSULATION & DUCT LINER ADHESIVE

Quick Adhesion

High Strength Bonding

Wide Web Spray



DANGER
 EXTREMELY FLAMMABLE.
 EYE IRRITANT.
 CONTENTS UNDER PRESSURE.
 FATAL IF SWALLOWED.

For Professional Use Only.
 Keep Out Of Reach Of Children.

Net Wt. 12oz.
 (340 Grams)

FEATURES:

This industrial-grade aerosol adhesive delivers exceptional bonding strength for a wide range of applications. Engineered with a high-solids formula and a wide web spray pattern, it provides consistent, controlled coverage with minimal overspray. Suitable for both temporary and permanent use, it adheres effectively to insulation, duct liner, leather, cardboard, cloth, and most plastics—even on uneven or porous surfaces. The adhesive dries clear, remains flexible under stress, and withstands harsh conditions. Formulated without chlorinated solvents or ozone-depleting compounds, it cleans easily with adhesive removers containing petroleum distillates or d-limonene.

BENEFITS:

- Wide web spray pattern for controlled, even application
- High solids formula delivers exceptional strength
- Bonds to uneven and porous materials
- Suitable for temporary or permanent applications
- Waterproof, flexible, and transparent finish
- Safe formulation with no chlorinated solvents or ozone depleters
- Quick and effective cleanup with citrus or petroleum-based adhesive removers

DIRECTIONS:

For use by HVACR professionals only.



Wear protective clothing and eyewear.



Shake well. Spray 4-6" from surface in an even, sweeping motion.



Allow 3-5 minutes of tack time before assembly.

ADVANCED DIRECTIONS:

TEMPORARY BONDS: Spray one surface, allow to become tacky then bond surfaces together. **PERMANENT BONDS:** Liberally spray both surfaces and material. Allow to tack, then bond. **CLEANUP:** When finishing the spray application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If the adhesive accumulates around nozzle wipe clear while wet. If dried in valve opening, remove with adhesive remover or replace actuator tip. To unclog tip or remove overspray, use an adhesive remover containing petroleum distillates and/or the citrus extract d-limonene.

**DANGER**

Extremely flammable aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fumes, gas, mist, vapors, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection and face protection.

RESPONSE: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

DISPOSAL: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

CONTAINS (CAS#): Propane (74-98-6), Acetone (67-64-1), Butane (106-97-8), Naphtha, (Petroleum), Hydrotreated Light (64742-49-0), n-Heptane (142-82-5), Methyl Acetate (79-20-9).

KEEP OUT OF REACH OF CHILDREN. NOT FOR SALE IN THE STATE OF CALIFORNIA.



1 3CFP5



MADE IN THE
USA
 WITH GLOBALLY
 SOURCED MATERIALS



Manufactured for: Nu-Calgon
 2611 Schuetz Rd.
 St. Louis, MO 63043
 Customer Service: 800-554-5499
 Chemical Emergency: 800-424-9300
www.nucalgon.com
 Calgon is a licensed trade name.
 (0925)

.093

.094

.437

22-0000



Youngstown Pre-Press, Inc.
 3691 LeHarps Road
 Youngstown, Ohio 44515
 PHONE: 330.793.3690

Date: 03.29.22	Job #: US-0000-0	Design/EO: 22-0000	Scans: N/A	Revisions:
Customer: SONOCO	Plant: WARNER	End User:	Part#: 0000000	
Design Name:	Filler:	Filler#:		