

BODY BLANK 8.150

Type Limits 7.700

**SONOCO METAL PACKAGING**  
211 X 713 CONO II N.I.

BODY BLANK HEIGHT 7.938"  
Color Limits 7.750  
Necked In Type Limits 7.001

4369-85

**Nu-Calgon**

**Spray-N-Bond LV**  
INSULATION AND DUCT LINER ADHESIVE  
LOW VOC

Quick Adhesion  
High Strength Bonding  
Wide Web Spray



**DANGER**  
EXTREMELY FLAMMABLE.  
EYE IRRITANT.  
CONTENTS UNDER PRESSURE.  
For Professional Use Only.  
Keep Out Of Reach Of Children.

Net Wt. 12oz.  
(340 Grams)

**FEATURES:**

This industrial-grade aerosol adhesive delivers exceptional bonding strength for a wide range of applications. Engineered with a high-solids formula and a wide web spray pattern, it provides consistent, controlled coverage with minimal overspray. Suitable for both temporary and permanent use, it adheres effectively to insulation, duct liner, leather, cardboard, cloth, and most plastics—even on uneven or porous surfaces. The adhesive dries clear, remains flexible under stress, and withstands harsh conditions. Formulated without chlorinated solvents or ozone-depleting compounds, it cleans easily with adhesive removers containing petroleum distillates or d-limonene.

**BENEFITS:**

- Wide web spray pattern for controlled, even application
- High solids formula delivers exceptional strength
- Bonds to uneven and porous materials
- Suitable for temporary or permanent applications
- Waterproof, flexible, and transparent finish
- Safe formulation with no chlorinated solvents or ozone depleters
- Quick and effective cleanup with citrus or petroleum-based adhesive removers

**DIRECTIONS:**

For use by HVACR professionals only.

Wear protective clothing and eyewear.

Shake well. Spray 4-6" from surface in an even, sweeping motion.

Allow 3-5 minutes of tack time before assembly.

**ADVANCED DIRECTIONS:**

**TEMPORARY BONDS:** Spray one surface, allow to become tacky then bond surfaces together.  
**PERMANENT BONDS:** Liberally spray both surfaces and material. Allow to tack, then bond. **CLEANUP:** When finishing the spray application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If the adhesive accumulates around nozzle wipe clear while wet. If dried in valve opening, remove with adhesive remover or replace actuator tip. To unclog tip or remove overspray, use an adhesive remover containing petroleum distillates and/or the citrus extract d-limonene.



**DANGER**

Extremely flammable aerosol. Pressurized container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

**PREVENTION:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fumes, gas, mist, vapors, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection and face protection. **RESPONSE: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**STORAGE:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

**DISPOSAL:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**CONTAINS (CAS#):** Acetone (67-64-1); Propane (74-98-6); Butane (106-97-8); Methyl Acetate (79-20-9); Naphtha, (Petroleum), Hydrotreated Light (64742-49-0); Benzene (71-43-2).

**KEEP OUT OF REACH OF CHILDREN**

**VOC INFORMATION:** Web Spray Adhesive. (VOC 40% by weight).  
PFAS Free formulation.

**WARNING:** This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



1 809NA2



MADE IN THE  
**USA**  
WITH GLOBALLY  
SOURCED MATERIALS



Manufactured for: Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
[www.nucalgon.com](http://www.nucalgon.com)  
Calgon is a licensed trade name.  
(0925)

22-0000



Youngstown Pre-Press, Inc.  
3691 LeHapps Road  
Youngstown, Ohio 44515  
PHONE: 330.793.3690

Date: 03.29.22	Job #: US-0000-0	Design/EO: 22-0000	Scans: N/A	Revisions:
Customer: SONOCO	Plant: WARNER	End User:	Part#: 0000000	
Design Name:	Filler:	Filler#:		