

4623-81


**DIRECTIONS**

Shut off water.



Unlock and remove old filter.



Install new filter.



Turn on water.



Flush with 5 gallons of water.

Replace cartridge every 6 months or sooner, should flow become less than desirable.

SPECIFICATIONS

Filters For:	17,500 gallons (66,244 liters)
Dimensions:	14.75" x 4" (37.5cm x 10.1cm)
Operating Pressure:	25-125 psi (0.7-8.6 bar)
Operating Temperature:	35-100°F (2-38°C)
Maximum Service Flow Rate:	1.67 gpm (6.32 lpm)
Micron Rating:	.5

Nu-Calgon
2611 Schuetz Rd. • St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
Calgon is a licensed trade name. (0426)

4623-81




Scale, Chlorine, Taste
& Odor Reduction

Microplastics, Cysts and .5 Micron
Particulate Reduction

Replaces Everpure®
MC² & XC²

Soda Fountain/Drinking Water

Use with OEM manifolds

DATE OF INSTALL:

4623-81


**NOTES**

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- Meets or exceeds the performance listed below for the cross-referenced Everpure® product.

Flow Rate	Meets
Micron Rating	Meets
Gallon Capacity	Exceeds

- Cartridge capacity may vary according to flow rate, inlet line pressure and local water conditions, which may require more frequent cartridge replacement.
- Install on cold water line only.



System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste and Odor and Nominal Particulate Class I, Standard 53 for Cyst, and Standard 401 for Microplastics.

MADE IN THE
USA
WITH GLOBALLY
SOURCED MATERIALS



This product is not manufactured, sponsored or affiliated with Everpure®.